

STARPOWER

SEMICONDUCTOR

IGBT

GD150TLL120C2S

1200V/150A 3-level in one-package

General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness.

They are designed for the applications such as UPS.

Features


- Low $V_{CE(sat)}$ SPT+ IGBT technology
- $V_{CE(sat)}$ with positive temperature coefficient
- Low switching loss
- Maximum junction temperature 175 °C
- Low inductance case
- Fast & soft reverse recovery anti-parallel FWD
- Isolated copper baseplate using DBC technology



Typical Applications

- Inverter for motor drive
- Uninterruptible power supply
- Solar power

Equivalent Circuit Schematic



Absolute Maximum Ratings $T_C=25^{\circ}\text{C}$ unless otherwise noted**T1,T2 IGBT**

Symbol	Description	Values	Unit
V_{CES}	Collector-Emitter Voltage	1200	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current @ $T_C=25^{\circ}\text{C}$	245	A
	@ $T_C=100^{\circ}\text{C}$	150	
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	300	A
P_D	Maximum Power Dissipation @ $T_j=175^{\circ}\text{C}$	938	W

D1,D2 Diode

Symbol	Description	Values	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	1200	V
I_F	Diode Continuous Forward Current	150	A
I_{FM}	Diode Maximum Forward Current $t_p=1\text{ms}$	300	A

T3,T4 IGBT

Symbol	Description	Values	Unit
V_{CES}	Collector-Emitter Voltage	650	V
V_{GES}	Gate-Emitter Voltage	± 20	V
I_C	Collector Current @ $T_C=25^{\circ}\text{C}$	185	A
	@ $T_C=65^{\circ}\text{C}$	150	
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	300	A
P_D	Maximum Power Dissipation @ $T_j=175^{\circ}\text{C}$	459	W

D3,D4 Diode

Symbol	Description	Values	Unit
V_{RRM}	Repetitive Peak Reverse Voltage	650	V
I_F	Diode Continuous Forward Current	150	A
I_{FM}	Diode Maximum Forward Current $t_p=1\text{ms}$	300	A

Module

Symbol	Description	Values	Unit
T_{jmax}	Maximum Junction Temperature	175	$^{\circ}\text{C}$
T_{jop}	Operating Junction Temperature	-40 to +150	$^{\circ}\text{C}$
T_{STG}	Storage Temperature Range	-40 to +125	$^{\circ}\text{C}$
V_{ISO}	Isolation Voltage RMS, $f=50\text{Hz}$, $t=1\text{min}$	4000	V
M	Terminal Connection Torque, Screw M6	2.5 to 5.0	N.m
	Mounting Torque, Screw M6	3.0 to 5.0	

T1,T2 IGBT Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=150\text{A}, V_{GE}=15\text{V}, T_j=25^\circ\text{C}$		2.00	2.45	V
		$I_C=150\text{A}, V_{GE}=15\text{V}, T_j=125^\circ\text{C}$		2.20		
		$I_C=150\text{A}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}$		2.30		
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=6.0\text{mA}, V_{CE}=V_{GE}, T_j=25^\circ\text{C}$	5.3	5.8	6.3	V
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			1.0	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			400	nA
R_{Gint}	Internal Gate Resistance			2.0		Ω
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}, f=1\text{MHz}, V_{GE}=0\text{V}$		10.6		nF
C_{res}	Reverse Transfer Capacitance			0.47		nF
Q_G	Gate Charge	$V_{GE}=-15 \dots +15\text{V}$		1.53		μC
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=150\text{A}, R_G=5.1\Omega, V_{GE}=\pm 15\text{V}, T_j=25^\circ\text{C}$		340		ns
t_r	Rise Time			70		ns
$t_{d(off)}$	Turn-Off Delay Time			442		ns
t_f	Fall Time			165		ns
E_{on}	Turn-On Switching Loss			8.00		mJ
E_{off}	Turn-Off Switching Loss			9.95		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=150\text{A}, R_G=5.1\Omega, V_{GE}=\pm 15\text{V}, T_j=125^\circ\text{C}$		355		ns
t_r	Rise Time			70		ns
$t_{d(off)}$	Turn-Off Delay Time			481		ns
t_f	Fall Time			311		ns
E_{on}	Turn-On Switching Loss			12.5		mJ
E_{off}	Turn-Off Switching Loss			15.3		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=150\text{A}, R_G=5.1\Omega, V_{GE}=\pm 15\text{V}, T_j=150^\circ\text{C}$		370		ns
t_r	Rise Time			75		ns
$t_{d(off)}$	Turn-Off Delay Time			500		ns
t_f	Fall Time			330		ns
E_{on}	Turn-On Switching Loss			13.4		mJ
E_{off}	Turn-Off Switching Loss			16.4		mJ
I_{SC}	SC Data	$t_p \leq 10\mu\text{s}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}, V_{CC}=900\text{V}, V_{CEM} \leq 1200\text{V}$		650		A

D1,D2 Diode Characteristics $T_c=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_F	Diode Forward Voltage	$I_C=150\text{A}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$		1.80	2.25	V
		$I_C=150\text{A}, V_{GE}=0\text{V}, T_j=125^\circ\text{C}$		1.85		
		$I_C=150\text{A}, V_{GE}=0\text{V}, T_j=150^\circ\text{C}$		1.85		
Q_r	Recovered Charge	$V_R=600\text{V}, I_F=150\text{A}, R_G=5.1\Omega, V_{GE}=-15\text{V}, T_j=25^\circ\text{C}$		13.4		μC
I_{RM}	Peak Reverse Recovery Current			143		A
E_{rec}	Reverse Recovery Energy			9.11		mJ
Q_r	Recovered Charge	$V_R=600\text{V}, I_F=150\text{A}, R_G=5.1\Omega, V_{GE}=-15\text{V}, T_j=125^\circ\text{C}$		26.1		μC
I_{RM}	Peak Reverse Recovery Current			178		A
E_{rec}	Reverse Recovery Energy			15.4		mJ
Q_r	Recovered Charge	$V_R=600\text{V}, I_F=150\text{A}, R_G=5.1\Omega, V_{GE}=-15\text{V}, T_j=150^\circ\text{C}$		30.0		μC
I_{RM}	Peak Reverse Recovery Current			190		A
E_{rec}	Reverse Recovery Energy			18.2		mJ

T3,T4 IGBT Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=150\text{A}, V_{GE}=15\text{V}, T_j=25^\circ\text{C}$		1.45	1.90	V
		$I_C=150\text{A}, V_{GE}=15\text{V}, T_j=125^\circ\text{C}$		1.60		
		$I_C=150\text{A}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}$		1.70		
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=2.4\text{mA}, V_{CE}=V_{GE}, T_j=25^\circ\text{C}$	5.1	5.8	6.4	V
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			1.0	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			400	nA
R_{Gint}	Internal Gate Resistance			2.0		Ω
C_{ies}	Input Capacitance	$V_{CE}=25\text{V}, f=1\text{MHz}, V_{GE}=0\text{V}$		9.24		nF
C_{res}	Reverse Transfer Capacitance				0.27	
Q_G	Gate Charge	$V_{GE}=-15 \dots +15\text{V}$		1.10		μC
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=300\text{V}, I_C=100\text{A}, R_G=3.3\Omega, V_{GE}=\pm 15\text{V}, T_j=25^\circ\text{C}$		84		ns
t_r	Rise Time			40		ns
$t_{d(off)}$	Turn-Off Delay Time			300		ns
t_f	Fall Time			88		ns
E_{on}	Turn-On Switching Loss			1.21		mJ
E_{off}	Turn-Off Switching Loss			4.14		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=300\text{V}, I_C=100\text{A}, R_G=3.3\Omega, V_{GE}=\pm 15\text{V}, T_j=125^\circ\text{C}$		102		ns
t_r	Rise Time			44		ns
$t_{d(off)}$	Turn-Off Delay Time			328		ns
t_f	Fall Time			130		ns
E_{on}	Turn-On Switching Loss			1.76		mJ
E_{off}	Turn-Off Switching Loss			5.09		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=300\text{V}, I_C=100\text{A}, R_G=3.3\Omega, V_{GE}=\pm 15\text{V}, T_j=150^\circ\text{C}$		110		ns
t_r	Rise Time			45		ns
$t_{d(off)}$	Turn-Off Delay Time			342		ns
t_f	Fall Time			139		ns
E_{on}	Turn-On Switching Loss			1.95		mJ
E_{off}	Turn-Off Switching Loss			5.40		mJ
I_{SC}	SC Data	$t_p \leq 6\mu\text{s}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}, V_{CC}=360\text{V}, V_{CEM} \leq 650\text{V}$		750		A

D3,D4 Diode Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_F	Diode Forward Voltage	$I_C=150\text{A}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$		1.55	2.00	V
		$I_C=150\text{A}, V_{GE}=0\text{V}, T_j=125^\circ\text{C}$		1.50		
		$I_C=150\text{A}, V_{GE}=0\text{V}, T_j=150^\circ\text{C}$		1.45		
Q_r	Recovered Charge	$V_R=300\text{V}, I_F=150\text{A}, R_G=3.3\Omega, V_{GE}=-15\text{V}, T_j=25^\circ\text{C}$		6.9		μC
I_{RM}	Peak Reverse Recovery Current			78		A
E_{rec}	Reverse Recovery Energy			1.41		mJ
Q_r	Recovered Charge	$V_R=300\text{V}, I_F=150\text{A}, R_G=3.3\Omega, V_{GE}=-15\text{V}, T_j=125^\circ\text{C}$		11.4		μC
I_{RM}	Peak Reverse Recovery Current			106		A
E_{rec}	Reverse Recovery Energy			2.49		mJ
Q_r	Recovered Charge	$V_R=300\text{V}, I_F=150\text{A}, R_G=3.3\Omega, V_{GE}=-15\text{V}, T_j=150^\circ\text{C}$		13.6		μC
I_{RM}	Peak Reverse Recovery Current			111		A
E_{rec}	Reverse Recovery Energy			3.00		mJ

Module Characteristics $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
$R_{\theta JC}$	Junction-to-Case (per T1,T2 IGBT)			0.160	K/W
	Junction-to-Case (per D1,D2 Diode)			0.276	
	Junction-to-Case (per T3,T4 IGBT)			0.327	
	Junction-to-Case (per D3,D4 Diode)			0.542	
$R_{\theta CS}$	Case-to-Sink (per T1,T2 IGBT)		0.165		K/W
	Case-to-Sink (per D1,D2 Diode)		0.285		
	Case-to-Sink (per T3,T4 IGBT)		0.338		
	Case-to-Sink (per D3,D4 Diode)		0.561		
$R_{\theta CS}$	Case-to-Sink		0.035		K/W
G	Weight of Module		340		g




Fig 1. T1,T2 IGBT Output Characteristics




Fig 2. T1,T2 IGBT Transfer Characteristics




Fig 3. T1,T2 IGBT Switching Loss vs. I_C




Fig 4. T1,T2 IGBT Switching Loss vs. R_G




Fig 5. T1,T2 RBSOA




Fig 6. T1,T2 IGBT Transient Thermal Impedance




Fig 7. D1,D2 Diode Forward Characteristics




Fig 8. D1,D2 Diode Switching Loss vs. I_F




Fig 9. D1,D2 Diode Switching Loss vs. R_G




Fig 10. D1,D2 Diode Transient Thermal Impedance




Fig 11. T3,T4 IGBT Output Characteristics




Fig 12. T3,T4 IGBT Transfer Characteristics




Fig 13. T3,T4 IGBT Switching Loss vs. I_C




Fig 14. T3,T4 IGBT Switching Loss vs. R_G




Fig 15. T3,T4 RBSOA




Fig 16. T3,T4 IGBT Transient Thermal Impedance




Fig 17. D3,D4 Diode Forward Characteristics




Fig 18. D3,D4 Diode Switching Loss vs. I_F




Fig 19. D3,D4 Diode Switching Loss vs. R_G




Fig 20. D3,D4 Diode Transient Thermal Impedance

Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.cc), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.