

# STARPOWER

SEMICONDUCTOR

**IGBT**

## GD200HFT120C2S\_G8

**1200V/200A 2 in one-package**

### General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as general inverters and UPS.

### Features


- Low  $V_{CE(sat)}$  Trench IGBT technology
- Low switching loss
- 10 $\mu$ s short circuit capability
- Low inductance case
- $V_{CE(sat)}$  with positive temperature coefficient
- Fast & soft reverse recovery anti-parallel FWD
- Isolated copper baseplate using DBC technology



### Typical Applications

- Inverter for motor drive
- AC and DC servo drive amplifier
- Uninterruptible power supply

### Equivalent Circuit Schematic



**Absolute Maximum Ratings**  $T_C=25^{\circ}\text{C}$  unless otherwise noted**IGBT**

Symbol	Description	Values	Unit
$V_{CES}$	Collector-Emitter Voltage	1200	V
$V_{GES}$	Gate-Emitter Voltage	$\pm 30$	V
$I_C$	Collector Current @ $T_C=25^{\circ}\text{C}$	330	A
	@ $T_C=100^{\circ}\text{C}$	200	
$I_{CM}$	Pulsed Collector Current $t_p=1\text{ms}$	400	A
$P_D$	Maximum Power Dissipation @ $T_j=175^{\circ}\text{C}$	1103	W

**Diode**

Symbol	Description	Values	Unit
$V_{RRM}$	Repetitive Peak Reverse Voltage	1200	V
$I_F$	Diode Continuous Forward Current	200	A
$I_{FM}$	Diode Maximum Forward Current $t_p=1\text{ms}$	400	A

**Module**

Symbol	Description	Values	Unit
$T_{jmax}$	Maximum Junction Temperature	175	$^{\circ}\text{C}$
$T_{jop}$	Operating Junction Temperature	-40 to +150	$^{\circ}\text{C}$
$T_{STG}$	Storage Temperature Range	-40 to +125	$^{\circ}\text{C}$
$V_{ISO}$	Isolation Voltage RMS, $f=50\text{Hz}$ , $t=1\text{min}$	4000	V
M	Terminal Connection Torque, Screw M6	2.5 to 5.0	N.m
	Mounting Torque, Screw M6	3.0 to 5.0	

**IGBT Characteristics**  $T_c=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit	
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=200\text{A}, V_{GE}=15\text{V}, T_j=25^\circ\text{C}$		1.70	2.15	V	
		$I_C=200\text{A}, V_{GE}=15\text{V}, T_j=125^\circ\text{C}$		1.95			
		$I_C=200\text{A}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}$		2.00			
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=8.0\text{mA}, V_{CE}=V_{GE}, T_j=25^\circ\text{C}$	5.0	5.8	6.5	V	
$I_{CES}$	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			5.0	mA	
$I_{GES}$	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			400	nA	
$R_{Gint}$	Internal Gate Resistance			1.0		$\Omega$	
$C_{ies}$	Input Capacitance	$V_{CE}=30\text{V}, f=1\text{MHz}, V_{GE}=0\text{V}$		18.2		nF	
$C_{res}$	Reverse Transfer Capacitance				0.56		nF
$Q_G$	Gate Charge	$V_{GE}=15\text{V}$		1.20		$\mu\text{C}$	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=200\text{A}, R_G=3.0\Omega, V_{GE}=\pm 15\text{V}, T_j=25^\circ\text{C}$		213		ns	
$t_r$	Rise Time			64		ns	
$t_{d(off)}$	Turn-Off Delay Time			280		ns	
$t_f$	Fall Time			180		ns	
$E_{on}$	Turn-On Switching Loss				4.10		mJ
$E_{off}$	Turn-Off Switching Loss				16.3		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=200\text{A}, R_G=3.0\Omega, V_{GE}=\pm 15\text{V}, T_j=125^\circ\text{C}$		285		ns	
$t_r$	Rise Time			78		ns	
$t_{d(off)}$	Turn-Off Delay Time			363		ns	
$t_f$	Fall Time			278		ns	
$E_{on}$	Turn-On Switching Loss				7.40		mJ
$E_{off}$	Turn-Off Switching Loss				23.0		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600\text{V}, I_C=200\text{A}, R_G=3.0\Omega, V_{GE}=\pm 15\text{V}, T_j=150^\circ\text{C}$		293		ns	
$t_r$	Rise Time			81		ns	
$t_{d(off)}$	Turn-Off Delay Time			374		ns	
$t_f$	Fall Time			327		ns	
$E_{on}$	Turn-On Switching Loss				8.70		mJ
$E_{off}$	Turn-Off Switching Loss				25.2		mJ
$I_{SC}$	SC Data	$t_p \leq 10\mu\text{s}, V_{GE}=15\text{V}, T_j=150^\circ\text{C}, V_{CC}=900\text{V}, V_{CEM} \leq 1200\text{V}$		800		A	

**Diode Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_F$	Diode Forward Voltage	$I_C=200\text{A}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$		2.15	2.55	V
		$I_C=200\text{A}, V_{GE}=0\text{V}, T_j=125^\circ\text{C}$		2.20		
		$I_C=200\text{A}, V_{GE}=0\text{V}, T_j=150^\circ\text{C}$		2.15		
$Q_r$	Recovered Charge	$V_R=600\text{V}, I_F=200\text{A}, R_G=3.0\Omega, V_{GE}=-15\text{V}, T_j=25^\circ\text{C}$		16.2		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			169		A
$E_{rec}$	Reverse Recovery Energy			10.2		mJ
$Q_r$	Recovered Charge	$V_R=600\text{V}, I_F=200\text{A}, R_G=3.0\Omega, V_{GE}=-15\text{V}, T_j=125^\circ\text{C}$		24.4		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			204		A
$E_{rec}$	Reverse Recovery Energy			16.2		mJ
$Q_r$	Recovered Charge	$V_R=600\text{V}, I_F=200\text{A}, R_G=3.0\Omega, V_{GE}=-15\text{V}, T_j=150^\circ\text{C}$		31.4		$\mu\text{C}$
$I_{RM}$	Peak Reverse Recovery Current			222		A
$E_{rec}$	Reverse Recovery Energy			19.4		mJ

**Module Characteristics**  $T_C=25^\circ\text{C}$  unless otherwise noted

Symbol	Parameter	Min.	Typ.	Max.	Unit
$L_{CE}$	Stray Inductance			20	nH
$R_{CC'+EE'}$	Module Lead Resistance, Terminal to Chip		0.35		m $\Omega$
$R_{\theta JC}$	Junction-to-Case (per IGBT)			0.136	K/W
	Junction-to-Case (per Diode)			0.194	
$R_{\theta CS}$	Case-to-Sink (per IGBT)		0.060		K/W
	Case-to-Sink (per Diode)		0.085		
$R_{\theta CS}$	Case-to-Sink		0.035		K/W
G	Weight of Module		300		g




Fig 1. IGBT Output Characteristics




Fig 2. IGBT Transfer Characteristics




Fig 3. IGBT Switching Loss vs.  $I_C$




Fig 4. IGBT Switching Loss vs.  $R_G$




Fig 5. RBSOA




Fig 6. IGBT Transient Thermal Impedance




Fig 7. Diode Forward Characteristics




Fig 8. Diode Switching Loss vs.  $I_F$




Fig 9. Diode Switching Loss vs.  $R_G$






Fig 10. Diode Transient Thermal Impedance

**Circuit Schematic**



**Package Dimensions**

Dimensions in Millimeters





## Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see [www.powersemi.cc](http://www.powersemi.cc)), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.  
Changes of this product data sheet are reserved.