

STARPOWER

SEMICONDUCTOR

IGBT

GD75PIT120C6S_G8

Molding Type Module

1200V/75A PIM in one-package

General Description

STARPOWER IGBT Power Module provides ultra low conduction loss as well as short circuit ruggedness. They are designed for the applications such as general inverter and UPS.



Features

- Low $V_{CE(sat)}$ Trench IGBT technology
- 10 μ s short circuit capability
- $V_{CE(sat)}$ with positive temperature coefficient
- Maximum junction temperature 175 °C
- Low inductance case
- Fast & soft reverse recovery anti-parallel FWD
- Isolated copper baseplate using DBC technology

Typical Applications

- Inverter for motor drive
- AC and DC servo drive amplifier
- Uninterruptible power supply

IGBT-inverter $T_C=25^\circ\text{C}$ unless otherwise noted**Maximum Rated Values**

Symbol	Description	GD75PIT120C6S_G8	Units
V_{CES}	Collector-Emitter Voltage @ $T_j=25^\circ\text{C}$	1200	V
V_{GES}	Gate-Emitter Voltage @ $T_j=25^\circ\text{C}$	± 30	V
I_C	Collector Current @ $T_C=25^\circ\text{C}$	130	A
	@ $T_C=100^\circ\text{C}$	75	
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	150	A
P_{tot}	Total Power Dissipation @ $T_j=175^\circ\text{C}$	416	W

Off Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{(BR)CES}$	Collector-Emitter Breakdown Voltage	$T_j=25^\circ\text{C}$	1200			V
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			5.0	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			400	nA

On Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=3.0\text{mA}, V_{CE}=V_{GE}, T_j=25^\circ\text{C}$	5.0	5.8	6.5	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=75\text{A}, V_{GE}=15\text{V}, T_j=25^\circ\text{C}$		1.70	2.15	V
		$I_C=75\text{A}, V_{GE}=15\text{V}, T_j=175^\circ\text{C}$		2.10		

Switching Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=75A,$ $R_G=1.5\Omega, V_{GE}=\pm 15V,$ $T_j=25^\circ C$		65		ns
t_r	Rise Time			15		ns
$t_{d(off)}$	Turn-Off Delay Time			200		ns
t_f	Fall Time			115		ns
E_{on}	Turn-On Switching Loss			3.20		mJ
E_{off}	Turn-Off Switching Loss			4.50		mJ
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=75A,$ $R_G=1.5\Omega, V_{GE}=\pm 15V,$ $T_j=125^\circ C$		70		ns
t_r	Rise Time			20		ns
$t_{d(off)}$	Turn-Off Delay Time			270		ns
t_f	Fall Time			240		ns
E_{on}	Turn-On Switching Loss			6.80		mJ
E_{off}	Turn-Off Switching Loss			6.50		mJ
C_{ies}	Input Capacitance	$V_{CE}=30V, f=1Mhz,$ $V_{GE}=0V$		6.90		nF
C_{oes}	Output Capacitance			0.42		nF
C_{res}	Reverse Transfer Capacitance			0.22		nF
R_{Gint}	Internal Gate Resister			2.0		Ω
Q_G	Gate Charge	$V_{CC}=600V, I_C=75A,$ $V_{GE}=15V$		466		nC
I_{SC}	SC Data	$t_p \leq 10\mu s, V_{GE}=15V,$ $T_j=125^\circ C, V_{CC}=900V,$ $V_{CEM} \leq 1200V$		450		A

Diode-inverter $T_C=25^\circ C$ unless otherwise noted

Maximum Rated Values

Symbol	Description	GD75PIT120C6S_G8	Units
V_{RRM}	Repetitive Peak Reverse Voltage @ $T_j=25^\circ C$	1200	V
I_F	DC Forward Current	75	A
I_{FRM}	Repetitive Peak Forward Current $t_p=1ms$	150	A

Characteristics Values

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units	
V_F	Diode Forward Voltage	$I_F=75A, V_{GE}=0V$	$T_j=25^\circ C$		1.65	2.10	V
			$T_j=125^\circ C$		1.65		
Q_r	Recovered Charge	$I_F=75A,$ $V_R=600V,$ $R_G=4.7\Omega,$ $V_{GE}=-15V$	$T_j=25^\circ C$		6.6		μC
			$T_j=125^\circ C$		13.1		
I_{RM}	Peak Reverse Recovery Current	$V_R=600V,$ $R_G=4.7\Omega,$ $V_{GE}=-15V$	$T_j=25^\circ C$		42		A
			$T_j=125^\circ C$		53		
E_{rec}	Reverse Recovery Energy	$V_R=600V,$ $R_G=4.7\Omega,$ $V_{GE}=-15V$	$T_j=25^\circ C$		2.41		mJ
			$T_j=125^\circ C$		4.73		

Diode-rectifier $T_C=25^\circ\text{C}$ unless otherwise noted**Maximum Rated Values**

Symbol	Description	GD75PIT120C6S_G8	Units
V_{RRM}	Repetitive Peak Reverse Voltage @ $T_j=25^\circ\text{C}$	1600	V
$I_{F(AV)}$	Average On-state Current @ $T_C=100^\circ\text{C}$	78	A
I_{RMSM}	Maximum RMS Current At Rectifier Output @ $T_C=80^\circ\text{C}$	120	A
I_{FSM}	Surge Forward Current $V_R=0\text{V}, t_p=10\text{ms}, T_j=45^\circ\text{C}$	1100	A
I^2t	I^2t -value, $V_R=0\text{V}, t_p=10\text{ms}, T_j=45^\circ\text{C}$	6050	A^2s

Characteristics Values

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_F	Diode Forward Voltage	$I_F=75\text{A}$ $T_j=150^\circ\text{C}$		1.10		V
I_R	Reverse Current	$T_j=150^\circ\text{C}, V_R=1600\text{V}$			3.0	mA

IGBT-brake-chopper $T_C=25^\circ\text{C}$ unless otherwise noted**Maximum Rated Values**

Symbol	Description	GD75PIT120C6S_G8	Units
V_{CES}	Collector-Emitter Voltage @ $T_j=25^\circ\text{C}$	1200	V
V_{GES}	Gate-Emitter Voltage @ $T_j=25^\circ\text{C}$	± 20	V
I_C	Collector Current @ $T_C=25^\circ\text{C}$ @ $T_C=100^\circ\text{C}$	80 40	A
I_{CM}	Pulsed Collector Current $t_p=1\text{ms}$	80	A
P_{tot}	Total Power Dissipation @ $T_j=175^\circ\text{C}$	325	W

Off Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{(BR)CES}$	Collector-Emitter Breakdown Voltage	$T_j=25^\circ\text{C}$	1200			V
I_{CES}	Collector Cut-Off Current	$V_{CE}=V_{CES}, V_{GE}=0\text{V}, T_j=25^\circ\text{C}$			5.0	mA
I_{GES}	Gate-Emitter Leakage Current	$V_{GE}=V_{GES}, V_{CE}=0\text{V}, T_j=25^\circ\text{C}$			400	nA

On Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	$I_C=2.4mA, V_{CE}=V_{GE}, T_j=25^\circ C$	5.0	6.1	7.5	V
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage	$I_C=40A, V_{GE}=15V, T_j=25^\circ C$		1.80	2.25	V
		$I_C=40A, V_{GE}=15V, T_j=125^\circ C$		2.00		

Switching Characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=40A, R_G=24\Omega, V_{GE}=\pm 15V, T_j=25^\circ C$		370		ns
t_r	Rise Time			84		ns
$t_{d(off)}$	Turn-Off Delay Time			334		ns
t_f	Fall Time			276		ns
E_{on}	Turn-On Switching Loss			5.45		mJ
E_{off}	Turn-Off Switching Loss		2.21		mJ	
$t_{d(on)}$	Turn-On Delay Time	$V_{CC}=600V, I_C=40A, R_G=24\Omega, V_{GE}=\pm 15V, T_j=125^\circ C$		375		ns
t_r	Rise Time			87		ns
$t_{d(off)}$	Turn-Off Delay Time			350		ns
t_f	Fall Time			328		ns
E_{on}	Turn-On Switching Loss			6.05		mJ
E_{off}	Turn-Off Switching Loss			3.45		mJ
C_{ies}	Input Capacitance	$V_{CE}=30V, f=1Mhz, V_{GE}=0V$		6.24		nF
C_{oes}	Output Capacitance			0.23		nF
C_{res}	Reverse Transfer Capacitance			0.15		nF
R_{Gint}	Internal Gate Resister			0		Ω
Q_G	Gate Charge	$V_{CC}=600V, I_C=40A, V_{GE}=15V$		232		nC
I_{SC}	SC Data	$t_p \leq 10\mu s, V_{GE}=15V, T_j=125^\circ C, V_{CC}=900V, V_{CEM} \leq 1200V$		500		A

Diode-brake-chopper $T_C=25^\circ\text{C}$ unless otherwise noted**Maximum Rated Values**

Symbol	Description	GD75PIT120C6S_G8	Units
V_{RRM}	Repetitive Peak Reverse Voltage @ $T_j=25^\circ\text{C}$	1200	V
I_F	DC Forward Current	35	A
I_{FRM}	Repetitive Peak Forward Current $t_p=1\text{ms}$	70	A

Characteristics Values

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
V_F	Diode Forward Voltage	$I_F=35\text{A}, V_{GE}=0\text{V}$	$T_j=25^\circ\text{C}$	1.90	2.30	V
			$T_j=125^\circ\text{C}$	1.80		
Q_r	Recovered Charge	$I_F=35\text{A}, V_R=600\text{V}, R_G=24\Omega, V_{GE}=-15\text{V}$	$T_j=25^\circ\text{C}$	1.7		μC
			$T_j=125^\circ\text{C}$	4.3		
I_{RM}	Peak Reverse Recovery Current	$I_F=35\text{A}, V_R=600\text{V}, R_G=24\Omega, V_{GE}=-15\text{V}$	$T_j=25^\circ\text{C}$	27		A
			$T_j=125^\circ\text{C}$	29		
E_{rec}	Reverse Recovery Energy	$I_F=35\text{A}, V_R=600\text{V}, R_G=24\Omega, V_{GE}=-15\text{V}$	$T_j=25^\circ\text{C}$	1.17		mJ
			$T_j=125^\circ\text{C}$	2.19		


Electrical Characteristics of NTC $T_C=25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Units
R_{25}	Rated Resistance			5.0		$\text{k}\Omega$
$\Delta R/R$	Deviation of R_{100}	$T_C=100^\circ\text{C}, R_{100}=493.3\Omega$	-5		5	%
P_{25}	Power Dissipation				20.0	mW
$B_{25/50}$	B-value	$R_2=R_{25}\exp[B_{25/50}(1/T_2-1/(298.15\text{K}))]$		3375		K

IGBT Module


Symbol	Parameter	Min.	Typ.	Max.	Units
V _{ISO}	Isolation Voltage RMS,f=50Hz,t=1min	4000			V
L _{CE}	Stray Inductance		60		nH
R _{CC'+EE'}	Module Lead Resistance,Terminal to Chip @ T _C =25°C		4.00		mΩ
R _{AA'+CC'}			2.00		
R _{θJC}	Junction-to-Case (per IGBT-inverter)			0.361	K/W
	Junction-to-Case (per Diode-inverter)			0.570	
	Junction-to-Case (per Diode-rectifier)			0.545	
	Junction-to-Case (per IGBT-brake-chopper)			0.461	
	Junction-to-Case (per Diode-brake-chopper)			1.061	
R _{θCS}	Case-to-Sink (Conductive grease applied)		0.009		K/W
T _{jmax}	Maximum Junction Temperature			175	°C
T _{jop}	Operating Junction Temperature	-40		150	°C
T _{STG}	Storage Temperature Range	-40		125	°C
Mounting Torque	Mounting Screw:M5	3.0		6.0	N.m
G	Weight of Module		300		g

Equivalent Circuit Schematic



Package Dimensions

Dimensions in Millimeters



Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. you and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. There will be no guarantee of any kind for the product and its characteristics.

Should you require product information in excess of the data given in this product data sheet or which concerns the specific application of our product, please contact the sales office, which is responsible for you (see www.powersemi.cc), For those that are specifically interested we may provide application notes.

Due to technical requirements our product may contain dangerous substances. For information on the types in question please contact the sales office, which is responsible for you.

Should you intend to use the Product in aviation applications, in health or live endangering or life support applications, please notify.

If and to the extent necessary, please forward equivalent notices to your customers.
Changes of this product data sheet are reserved.